



1615 Robertson Road  
PO Box 457  
Moberly, MO 65270  
800-568-1067  
Fax 800-881-3806  
dave@pepcoinc.com



# Steel Series

## Specifications

- 11 gauge 1.5" square A500 steel tubing legs, 14 gauge 1"x2" A500 steel tubing aprons with fillet welded cross brace.
- Each table consists of 3 parts, welded H-Frame top assembly and welded leg assemblies which slide into the top frame and are fastened by (8) 3/8" x 3/4" knife thread flanged hex bolts, four per side through specially designed 7-gauge threaded A500 welded assembly flanges yielding a fully unitized table frame
- Electro statically applied epoxy powder coated steel frame in black, textured for scratch resistance.
- 3/8" x 16 threaded inserts with 1.5" diameter steel glides, adjustable to 1.5" for floor leveling purposes.
- *ADA compliant knee clearance on 30" table height.*
- Tops are mounted to steel frame with mechanical and proprietary adhesive fastening
- *15-Year Warranty*, bar code product ID on every table ties into our computer system to the customer P.O., purchase date, and product ID.
- Tables ship KDF (knocked down flat) on narrow pallets for efficient handling, thereby minimizing freight damage. Instructions included for easy straightforward assembly at the job site.



## Options

- **Top Materials:**
  - Solid epoxy resin std 3/4" or 1"
  - Solid phenolic resin std 3/4" or 1"
- **Adjustable height option in 1" increments with steel leg inserts.**  
(29" - 41")
- **Casters—C4 or C2**
  - 4 swivel double locking or 2 fixed
- **GFCI Electrical Outlets**  
(1-4)
- **Greenlaw overhead rod assembly**
- **Frame color options available**